




DIRECTIONAL VALVE (Manual Rotary, 3-Way, 2-Position, 0° - 90°)

Ordering Code: **DR-10W-X-Y-Z**


Cartridge Retainer Kit
Ordering Code:
7ZE2540C002



Manifold
Ordering Code:
ML-10W3-X-AC01



Illustrations / detail are for reference only. Data subject to change.




Y

OPERATION

13

3-Way, 2-Position, Port ③ to Port ① (Turn CCW), Port ② to Port ① (Turn CW)



TECHNICAL DATA

Max. Operating pressure: 240 bar
(Refer To Performance Chart)

Rated flow: 38 l/min
(Refer To Performance Chart)

Cavity-Tooling: 10W-3

Installation torque: 35 - 45 Nm

Weight: 0.301 (Z=R-1) kg

- Manual Rotary Components Installation Instructions: Please refer Winner accessories. (J.990.123.E Directional Valve Manual Rotary Components - Installation Instructions)
- If you need to order lever separately or other specification, please contact the Winner sales department.

X

STRUCTURE

3A

3-Way, 2-Position, 0° - 90°
(2-Position Detent)


- Maximum Leakage Approximately (80 cc/min./240 bar)(VG32, 40°C)

Z

OPTIONS

(Blank)	Without Control Accessory Weight: 0.139 kg	
R	Manual Rotation Control Accessory (Without Lever) Weight: 0.245 kg	
R-1	Manual Rotation With Lever Control Accessory Length: 68 mm Weight: 0.301 kg	
R-2	Manual Rotation With Lever Control Accessory Length: 26 mm Weight: 0.267 kg	


DR-10W-3A-13



UNIT:mm

Illustrations / detail are for reference only. Data subject to change.

TRANSITION:



- 3-Way, 2-Position, During cross-over transition, all ports are blocked.